

Rear Toe Arms Kit Installation Instructions SPL RTA G29

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	22706	RTA Dogbone	2
2	90010	Aluminum Clamp	4
3	JM10T	FK Rod End	2
4	JML10T	FK Rod End	2
5	14-20-75SHCS Ti	0.75" Titanium Socket Head Cap Screw	4
6	90111	Rear Toe Link Spacer	8

RTA G29



Thank you for your purchase of this SPL Parts performance suspension product. Please follow these instructions exactly to ensure that the product is able to function to the best of its ability, and you can achieve the most performance out of your vehicle.

TOOLS NEEDED:

18mm socket and wrench 19mm Socket 3/16 allen wrench

1. Remove the OEM arm



2. Set SPL Parts Rear Toe Arm next to the OEM arm. Use the bolts through the stock arm to set the SPL Parts Arm to the exact length of the OEM arm ensuring equal thread engagement on both ends. **Note:** the groove on one side of the arm to indicate the left-hand threaded side.

3. Install the SPL Parts Arm using OEM hardware at the knuckle first. The shorter rod end (4) should be installed at the knuckle. This makes adjusting the arm much easier, as it moves the clamp (5) outside of the subframe clevis. Tighten this to end to 74 **ft-lb. DO NOT OVERTORQUE!** *SPL Parts is not liable for any issues due to overtorque.*
4. Place the arm in the clevis on the subframe side and line the hole up in the middle of the slot made for the eccentric. Install the provided Eccentric Lockout Washers (7) on the back side of the subframe and place the bolt through. It should fit between the two grooves in the subframe and prevent the bolt from moving. This will allow you to line up the other side which is buried in the subframe. Once you have both eccentrics lined up, tighten the nut (8) up to 74 **ft.-lb.**
5. Have your car professionally aligned as it is nearly impossible to replicate the original settings. Take your vehicle to an alignment shop, and bring these instructions with you to ensure that the arm is adjusted correctly.
6. Be safe and enjoy your new upgrade.



ONE-YEAR LIMITED WARRANTY AND DISCLAIMER

All SPL brand products are intended for **Off Road Use Only** and carry a one year limited warranty. See below for details. All other branded products carry their respective manufacturer warranty.

SPL PRO suspension products warranted to be free of defects in material and workmanship for one (1) year from the date of purchase.

If a product fails to meet specifications, SPL PARTS INC will, at its election, repair, replace, or make appropriate adjustment, if SPL PARTS INC determines to its satisfaction that the product is defective in material or workmanship, i.e. contains a defect arising out of the manufacture of the product and not a defect caused by other circumstances, including, but not limited to accident, misuse, abuse, unforeseeable use, neglect, alteration, improper installation, improper adjustment, improper repair, or failure caused by other equipment or interaction with other equipment. SPL PARTS INC is not responsible for labor charges, removal charges, installation, or other incidental or consequential costs. In no event shall the liability of SPL PARTS INC exceed the purchase price of the product.

SPL PARTS INC makes no other warranties, either expressed or implied, including limitation warranties as to merchantability or fitness for a particular purpose. SPL PARTS INC shall not be liable for, and buyer assumes all risk of, any advice or failure to provide advice by SPL PARTS INC to buyer regarding the product or use and installation of product. SPL PARTS INC shall not be liable for any special, incidental or consequential damages.

If the purchaser of the product shall fail to pay when due any portion of the purchase price, or fail to meet any terms required under contract agreed on at time of purchase, all warranties and remedies granted may be terminated.

Using any SPL arm as a tie/strap down point for a dyno session or transport will void the warranty.